


SBLE 1450 - Cell data sheet

Classification

Brand	Saft
Cell type	SBLE 1450
Cell P/N	311033071
Capacity at 5 hours rate	1,450 Ah
IEC Designation	KL1450P
According to	IEC 60623

Wiring principle



Crosswise

Physical data

Overall height	411 mm		
Cell height	410 mm		
Width	195 mm	Weight per cell	60.2 Kg
Length	463 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	6
Separator type	Grid	Terminal material	Steel
Connection torque	30.0 +/- 3.0 Nm	Vent type	Flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	150 cm3
Electrolyte per cell: Liquid	15.8 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



SBLE 1450 - Cell data sheet

Charging

Float voltage	1.42 V/Cell	High rate voltage (recommended)	1.47 V/Cell
Single-level voltage	1.43 V/Cell		

Resistance/Short circuit

Internal resistance	0.11 mOhm	Short circuit current	12062 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	149	185	290	464	619	745	955	1,232	1,381	1,483	1,594	1,828	2,030	2,175	2,610	2,805
1.05	148	184	287	450	561	640	799	1,042	1,151	1,194	1,326	1,514	1,633	1,784	2,143	2,326
1.1	145	178	273	378	475	547	646	811	876	961	1,058	1,111	1,330	1,450	1,765	1,935
1.14	142	167	240	328	393	436	502	642	687	713	802	933	1,084	1,185	1,475	1,633
1.16	133	152	208	281	336	363	412	540	601	649	711	851	989	1,081	1,345	1,489

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	173	211	324	496	648	771	976	1,244	1,389	1,489	1,597	1,828	2,030	2,175	2,610	2,805
1.05	172	212	326	495	608	688	852	1,101	1,214	1,258	1,395	1,590	1,715	1,873	2,251	2,443
1.1	170	207	315	428	533	611	717	896	966	1,059	1,165	1,222	1,463	1,595	1,942	2,129
1.14	166	196	281	379	453	500	575	733	785	814	915	1,064	1,236	1,351	1,682	1,862
1.16	156	179	244	329	391	423	479	627	697	753	825	987	1,147	1,254	1,561	1,728



SBLE 1450 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9.7	7.85	5.00	3.12	2.34	1.95	1.52	1.18	1.05	0.98	0.91	0.79	0.71	0.67	0.56	0.52
1.05	9.8	7.88	5.05	3.23	2.58	2.26	1.81	1.39	1.26	1.21	1.09	0.96	0.89	0.81	0.68	0.62
1.1	10.0	8.16	5.31	3.83	3.05	2.65	2.25	1.79	1.66	1.51	1.37	1.31	1.09	1.00	0.82	0.75
1.14	10.2	8.68	6.04	4.42	3.69	3.33	2.89	2.26	2.11	2.03	1.81	1.55	1.34	1.22	0.98	0.89
1.16	10.9	9.5	6.98	5.15	4.32	3.99	3.52	2.69	2.41	2.23	2.04	1.70	1.47	1.34	1.08	0.97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8.38	6.87	4.47	2.92	2.24	1.88	1.49	1.17	1.04	0.97	0.91	0.79	0.71	0.67	0.56	0.52
1.05	8.41	6.83	4.45	2.93	2.38	2.11	1.70	1.32	1.19	1.15	1.04	0.91	0.85	0.77	0.64	0.59
1.1	8.55	7.01	4.60	3.39	2.72	2.37	2.02	1.62	1.50	1.37	1.24	1.19	0.99	0.91	0.75	0.68
1.14	8.71	7.41	5.17	3.82	3.20	2.90	2.52	1.98	1.85	1.78	1.58	1.36	1.17	1.07	0.86	0.78
1.16	9.27	8.09	5.94	4.41	3.71	3.43	3.03	2.31	2.08	1.93	1.76	1.47	1.26	1.16	0.93	0.84

