


# SBLE 600 - Cell data sheet

## Classification

Brand	Saft
Cell type	SBLE 600
Cell P/N	310547471
Capacity at 5 hours rate	600 Ah
IEC Designation	KL600P
According to	IEC 60623

Wiring principle



Crosswise

## Physical data

Overall height	411 mm		
Cell height	410 mm		
Width	195 mm	Weight per cell	26.1 Kg
Length	206 mm		

## Construction

Container material	Polypropylene	No. of terminals/polarity	3
Separator type	Grid	Terminal material	Steel
Connection torque	30.0 +/- 3.0 Nm	Vent type	Flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

## Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

## Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	75 cm <sup>3</sup>
Electrolyte per cell: Liquid	6.3 liters		

## Connection

Cable area of internal connection cables	70 mm <sup>2</sup>	End-lug (and external cable)	35 mm <sup>2</sup>
--	--------------------	------------------------------	--------------------

# SBLE 600 - Cell data sheet

## Charging

---

Float voltage	1.42 V/Cell	High rate voltage (recommended)	1.47 V/Cell
Single-level voltage	1.43 V/Cell		

## Resistance/Short circuit

---

Internal resistance	0.28 mOhm	Short circuit current	4991 A
---------------------	-----------	-----------------------	--------

## Performance data

---

### Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	61.8	76.4	120	192	256	308	395	510	571	614	660	757	840	900	1,080	1,161
1.05	61.3	76.2	119	186	232	265	331	431	476	494	549	626	676	738	887	963
1.1	60.0	73.6	113	157	197	226	267	336	363	398	438	460	550	600	730	801
1.14	58.7	69.1	99.4	136	163	180	208	266	284	295	332	386	449	490	610	676
1.16	55.1	63.1	86.0	116	139	150	170	223	249	269	294	352	409	447	557	616

### Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	71.6	87.3	134	205	268	319	404	515	575	616	661	757	840	900	1,080	1,161
1.05	71.4	87.8	135	205	252	285	352	456	502	520	577	658	709	775	931	1,011
1.1	70.1	85.6	130	177	220	253	297	371	400	438	482	506	606	660	804	881
1.14	68.9	81.0	116	157	187	207	238	303	325	337	379	440	512	559	696	770
1.16	64.7	74.2	101	136	162	175	198	259	288	312	341	409	475	519	646	715

# SBLE 600 - Cell data sheet

## Kt Factor

---

### Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9.7	7.85	5.00	3.12	2.34	1.95	1.52	1.18	1.05	0.98	0.91	0.79	0.71	0.67	0.56	0.52
1.05	9.8	7.88	5.05	3.23	2.58	2.26	1.81	1.39	1.26	1.21	1.09	0.96	0.89	0.81	0.68	0.62
1.1	10.0	8.16	5.31	3.83	3.05	2.65	2.25	1.79	1.66	1.51	1.37	1.31	1.09	1.00	0.82	0.75
1.14	10.2	8.68	6.04	4.42	3.69	3.33	2.89	2.26	2.11	2.03	1.81	1.55	1.34	1.22	0.98	0.89
1.16	10.9	9.5	6.98	5.15	4.32	3.99	3.52	2.69	2.41	2.23	2.04	1.70	1.47	1.34	1.08	0.97

### Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1.5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8.38	6.87	4.47	2.92	2.24	1.88	1.49	1.17	1.04	0.97	0.91	0.79	0.71	0.67	0.56	0.52
1.05	8.41	6.83	4.45	2.93	2.38	2.11	1.70	1.32	1.19	1.15	1.04	0.91	0.85	0.77	0.64	0.59
1.1	8.55	7.01	4.60	3.39	2.72	2.37	2.02	1.62	1.50	1.37	1.24	1.19	0.99	0.91	0.75	0.68
1.14	8.71	7.41	5.17	3.82	3.20	2.90	2.52	1.98	1.85	1.78	1.58	1.36	1.17	1.07	0.86	0.78
1.16	9.27	8.09	5.94	4.41	3.71	3.43	3.03	2.31	2.08	1.93	1.76	1.47	1.26	1.16	0.93	0.84

